



## BEARING-MALAYCYA SDN.BHD.

### 5SRS15GM+[44-1000/1]LM THK Miniature Linear Guide Full Ball SRS-G Accuracy and Preload Selectable

Bearing No. 5SRS15GM+[44-1000/1]LM

Days to Ship	3 Days
Block Type	[Standard] M: Compact
The number of LM blocks combined with a axis	5
Nominal Part Number	15
Rail Type	Standard
Rail Width W1	15 mm
Mounting Height M	16 mm
Rail Length L	44 ~ 1000 mm
Radial Clearance	Normal
Accuracy Grade	Normal Grade (Best Leadtime)
Rolling Element	Ball
Basic Load Rating Dynamic Rating C(N)	5590
Basic Load Rating Static Rating Co(N)	5720
Allowable Static Moment MA(N m)	24.8
Allowable Static Moment MB(N m)	24.8
Allowable Static Moment MC(N m)	40.6
Symbols for Dust Resistance	None (Not Recommended)
Block external dimension W	32 mm
Block external dimension L	43 mm

5SRS15GM+[44-1000/1]LM Bearing 2D drawings and 3D CAD models



## BEARING-MALAYCYA SDN.BHD.

Number of Block Mounting Holes(holes)	4
Mounting Hole Dimension S(M)	M3
Mounting Hole Screw Depth	3.5 mm
Block dimension L1	25.7 mm