



BEARING-MALAYCYA SDN.BHD.

5SRS20M[SS,SSHH,UU]+[51-900/1]L[H, P]M THK Miniature Linear Guide Caged Ball SRS Series

Bearing No. 5SRS20M[SS,SSHH,UU]+[51-900/1]L[H,P]M

Days to Ship	22 Days
Block Type	[Standard] M: Compact
The number of LM blocks combined with a axis	5
Nominal Part Number	20
Rail Type	Standard
Rail Width W1	20 mm
Mounting Height M	20 mm
Rail Length L	51 ~ 900 mm
Radial Clearance	Normal
Accuracy Grade	High Grade / Precision Grade
Rolling Element	Ball
Basic Load Rating Dynamic Rating C(N)	7750
Basic Load Rating Static Rating Co(N)	9770
Allowable Static Moment MA(N m)	54.3
Allowable Static Moment MB(N m)	62.4
Allowable Static Moment MC(N m)	104
Symbols for Dust Resistance	SS: End and Side Seals / UU: End Seals (Best Leadtime)
Advanced Seal Options	SSHH: SS + Laminated

5SRS20M[SS,SSHH,UU]+[51-900/1]L[H,P]M
Bearing 2D drawings and 3D CAD models



BEARING-MALAYCYA SDN.BHD.

(Longer Leadtime)	Contact Scraper LaCS
Block external dimension W	40 mm
Block external dimension L	50 mm
Number of Block Mounting Holes(holes)	4
Mounting Hole Dimension S(M)	M4
Mounting Hole Screw Depth	6 mm
Block dimension L1	34 mm