



BEARING-MALAYCYA SDN.BHD.

5SRS20M+[51-900/1]L[H,P]M THK Miniature Linear Guide Caged Ball SRS Series

Bearing No. 5SRS20M+[51-900/1]L[H,P]M

| | |
|--|------------------------------|
| Days to Ship | 22 Days |
| Block Type | [Standard] M: Compact |
| The number of LM blocks combined with a axis | 5 |
| Nominal Part Number | 20 |
| Rail Type | Standard |
| Rail Width W1 | 20 mm |
| Mounting Height M | 20 mm |
| Rail Length L | 51 ~ 900 mm |
| Radial Clearance | Normal |
| Accuracy Grade | High Grade / Precision Grade |
| Rolling Element | Ball |
| Basic Load Rating Dynamic Rating C(N) | 7750 |
| Basic Load Rating Static Rating Co(N) | 9770 |
| Allowable Static Moment MA(N m) | 54.3 |
| Allowable Static Moment MB(N m) | 62.4 |
| Allowable Static Moment MC(N m) | 104 |
| Symbols for Dust Resistance | None (Not Recommended) |
| Block external dimension W | 40 mm |
| Block external dimension L | 50 mm |
| Number of Block Mounting | 4 |

5SRS20M+[51-900/1]L[H,P]M Bearing 2D drawings and 3D CAD models



BEARING-MALAYCYA SDN.BHD.

| | |
|---------------------------------|-------|
| Holes(holes) | |
| Mounting Hole Dimension S(M) | M4 |
| Mounting Hole Screw Depth | 6 mm |
| Block dimension L1 | 34 mm |