



BEARING-MALAYCYA SDN.BHD.

8HR1530+[70-1600/1]L THK Separated Linear Guide Side Rails Set Model HR

Bearing No. 8HR1530+[70-1600/1]L

Days to Ship	42 Days
Rail Width W1	10.7 mm
Mounting Height M	15 mm
Number of blocks	8
Material	Carbon Steel
Rail Length L	70 ~ 1600 mm
Accuracy Grade	Standard Grade
Callout Size	1530
Rolling Element	Ball
Basic Load Rating Dynamic Rating C(N)	4310
Basic Load Rating Static Rating Co(N)	7650
Allowable static moment MA(N · m)	98.2
Allowable static moment MB(N · m)	98.2
The outside dimension W of block	19.2 mm
The outside dimension L of block	69 mm
Mounting Hole Dimension S(M)	M4
The dimension L1 of bocks	40 mm
LM Block Surface Treatment (* Surface treatment that differs between the rail and block or only on the rail or block	Not Provided

8HR1530+[70-1600/1]L Bearing 2D drawings and 3D CAD models



BEARING-MALAYCYA SDN.BHD.

is not available.)	
LM Rail Surface Treatment (* Surface treatment that differs between the rail and block or only on the rail or block is not available.)	Not Provided